

CAT C7.1HPU TECHNICAL SPECIFICATIONS

- 173HP @ 2200 RPM
- 12v start and charging system
- Heavy duty cooling system with suction fan and guard
- Dry element remote mount Donaldson air



- | | |
|--|--|
| <ul style="list-style-type: none"> cleaner • SAE #3 flywheel housing w11.5 " flywheel (2.83 " pilot) | <ul style="list-style-type: none"> • Front and rear mounting support • Electric fuel pump • Electronic engine control |
|--|--|

Meets U.S. EPA Tier 3 equivalent (Tier 4 available) and EU Stage IIIA equivalent emission standards. Available using U.S. EPA Flexibility or EU Flexibility, and for other regulated and non-regulated areas.

World-class manufacturing capability and processes coupled with proven core engine designs assure reliability, quiet operation, and many hours of productive life.

- | | |
|--|---|
| <ul style="list-style-type: none"> • Hydraulic Reservoir Capacity • Diesel Tank Capacity • Hydraulic Pump Oilgear PVG 100 • Pump Flow at 1800 RPM: • Remote Adjustable Pump Pressure Control: • Pump Safety Manifold Containing: • Directional Control Valve: • Pressure Gauge • Return Filter: • Tank Breather • Pump Controls, Remote Pressure Compensation, Maximum Volume Stop • Remote Joystick Control for directional valve in operator 's console • Remote Pump Pressure On/Off Control • Optional Features include heat exchanger, drip pan, headache rack, air type with remote pump for continuous oil circulation | <p>120 US Gallons</p> <p>65 US Gallons</p> <p>6.0 CIR 5800 PSI Max 5000PSI Continuous</p> <p>43.25 GPM</p> <p>200-5000PSI</p> <p>Pressure Relief, Outlet Check Valve, Reducing Valve</p> <p>Remote Controlled, Rated Flow 120 GPM</p> <p>0-6000 PSI with 4 " Dial</p> <p>In Tank 300 GPM 10 Micron</p> <p>10 Micron</p> |
|--|---|